

M/T Ternfjord

› <http://terntank.com/ship/m-t-ternfjord/>



GENERAL:

Builder: Avic Dingheng Shipbuilding co. LTD, Cina 2016

Class notation: BV XHULL, XMACH, OIL Tanker, Chemical Tanker Dualfuel,ESP, Unrestricted Navigation, ICE CLASS 1A, XAUT-UMS, SYSNEQ, MON-SHAFT, VCS, INWATERSURVEY, CLEANSHIP

PARTICULARS:

Imo No: 9722405

Flag: DIS

Call Sign: OWPW2

Length Overall: 147.00 m

Length Between Perpendicular: 143.50 m

Breath (moulded): 22.00 m

Depth (moulded): 11.70 m

Draught (scantling): 9.00 m

Deadweight (at scantling draught): 15.000 t

Gross tonnage: 11.374 t

Net tonnage: 4.780 t

Hull no: AD0025

Design: Rolls-Royce Marine AS, type NVC 615 CT

Consumption: 12.0 knots 8.9 tonst LNG/Day

Marine gas oil: 610m3

Cargo tank capacity 98%: 16.548m3

Ballast water tanks: 6.636m3

LNG fuel storage tanks: 630m3

Marine gas oil: 610m3

Slop tanks: 242m3

Tech fresh water tanks: 325m3

Urea: 52m3

Tank coating: MarineLine784

Cargo Pumps: Deepwell pumps type DW 200/250 multisuction. Frequency controlled 450 m3/h at 120 m.l.c.

Cargo Alarm & monitoring systems:

Kongsberg Tank Radar, K-Chief 600 alarm, monitoring & control system, Operator station-OS. Kockumation Loading computer.

Inertgas System:

The Inertgas system is using one existing dedicated Thermal oil heater with a burner modified to also be able to generate Inertgas. Capacity 3950 m3/h.

Nitrogen System:

A N2 generator, cap. abt. 100 Nm3/h @ 96% N2 installed in ER. N2 buffer tank of about 20 m3 for Cargo handling. Buffer tank serving dual fuel machinery in ER also installed.

Balast water treatment:

Panasia GloEn-Patrol? BWMS is a combined treatment system taking advantage of Filter and UV units most environmentally friendly and optimally designed. Treatment Capacity: 1200m3/hr x 1 set

Bowthruster:

1 Tunnel Thruster 1650 AUX CP 865 kW 60Hz. DNV Class notation Ice 1A.

Main Engine:

Wärtsilä 5RT-flex 50 DF 5.850 kW 102 RPM 2-stroke, low pressure, LNG dual-fuel engine.

Fuel management:

Kongsberg fuel performance system, Shaft Torque/Power, Fuel Index, Ships speed, Fuel flowmeters.

Auxiliary Diesel:

GENERATOR SET DATA 3 x Mitsubishi MAS 850-S, 790 kW @ 1800rpm, 60Hz

Catamiser:

Combined exhaust gas heat recovery and SCR for NOx reduction below Tier III

Shaft Generator:

Permanent Magnet Shaft Generator with Variable Frequency Drive to allow running the Engine/Propeller in Combinator mode for optimum efficiency. Rated output shaft generator PTO 780 kW / PTI 1000 Kw.